

Material Safety Data Sheet



May Be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910. 1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved, OMB No. 1218-0072

Adopted

<p>IDENTITY (As Used on Label and List) Category B Stones – Travertine, Marble, Limestone Onyx</p>	<p>Note: Blank Spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</p>
---	---

Section I – Manufacturer & Distribution Information

<p>Manufacturer's Name FBR Mermer San. Tic. A.S.</p>	<p>Emergency Telephone Number (760) 801-8239</p>
<p>Yucebag mahallesi 834 Sokak, No. 9 Sengul Is Merkezi, Kat. 1, d. 37,</p>	<p>Telephone Number for Information (866) 728-2418</p>
<p>Denizli, Turkey</p>	<p>Date Prepared April 16, 2019</p>
<p>Distributor's Name FBR Marble, Inc.</p>	<p>Signature of Preparer (Optional)</p>
<p>6851 N. Paramount Blvd. Long Beach, CA 90805</p>	<p>Distributor's Telephone Number (562) 602-2300</p>

Section II – Hazard Ingredients/Identity Information

<p>Hazardous Components</p>	<p>Category B Stones</p>
<p>Specific Chemical Identity</p>	<p>CaCO₃/CaMg(CO₃)₂</p>
<p>Common Name</p>	<p>Calcite/Dolomite</p>
<p>OSHA PEL</p>	<p>NA</p>
<p>ACGIH TL V</p>	<p>NA</p>
<p>Other Limits</p>	<p>NA</p>
<p>% Optional</p>	<p>NA</p>
<p>Permissible Exposure Limit</p>	<p>1.0 mg/m³</p>

Note: Dimension stone is an inert material in its undisturbed or finished state. Only when natural stone is worked is there a potential for release of dust.

Section III – Physical/Chemical Characteristics

<p>Boiling point</p>	<p>NA</p>
<p>Vapor Pressure (mm Hg)</p>	<p>NA</p>
<p>Vapor Density (Air-1)</p>	<p>NA</p>
<p>Specific Gravity</p>	<p>2.0 to 4.0</p>
<p>Melting Point</p>	<p>NA</p>
<p>Solubility in Water</p>	<p>Not Soluble</p>

Appearance	Basic Stone Color
Odor	None

Section IV – Fire and Explosion Hazard Data

Flash Point (method used)	NA
Extinguishing Media	None. Non Flammable
Special Fire Fighting Procedures	None required
Unusual Fire & Explosion Hazards	None required

Section V – Reactivity Data

Stability	Stable
Incompatibility (Materials to Avoid)	All Acids
Hazardous Decomposition	NA
Hazardous Polymerization	Will Not Occur

Section VI – Health Hazard Data

Route(s) of Entry:	Inhalation <u>Yes</u>	Skin? None	Ingestion? None known
Health Hazards (Acute and Chronic)			
Acute – Excessive exposure to tile dust can cause eye, skin, and lung irritation from mechanical abrasion.			
Chronic – Not applicable for intact tiles. Excessive exposure to tile dust can cause discomfort and mechanical Irritation.			
Signs and Symptoms of Exposure			
Excessive exposure to tile dust can cause eye, skin, and lung irritation from mechanical abrasion.			
Medical Conditions Generally Aggravated By Exposure			
Existing lung disease may be aggravated after exposure to tile dusts.			
Emergency & First Aid Procedures			
Inhalation: If exposed to large amounts of tile cutting dust go or take victim outdoors to fresh air. Administer Artificial respiration if victim stops breathing. Keep victim at rest. Call for prompt medical attention.			
Ingestion: Not applicable for intact tiles.			
<i>*Have emergency eyewash station available in area where tiles are cut.</i>			

Section VII – Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled	Not considered Hazardous Waste
Waste Disposal Method	Normal Method for Non Hazardous Waste
Precautions to Be Taken in Handlin and Storing	Safety Toe Shoes where toes/feet are exposed to rolling or falling objects
Other Precautions	None

Section VIII – Control Measures

Respiratory Equipment	Yes
Local Exhaust Ventilation	Recommended
Protective Gloves	Not required for dust
Other protection, clothing or equipment	Safety Toe Shoes where toes/feet are exposed to rolling or falling objects. Eye protection